



COOLERS COMPARISON

Europe

MARCH 2024



COOL xs

COOL

	Production	Cold Drinks	Cold Drinks
	Refrigerant Gas	R134a	R134a
	Volts	220 -240V / 50Hz	220 -240V / 50Hz
	Production Speed (15°C product temperature)	50 minutes	90 - 120 minutes
1 tank	Capacity	-	19 l. (1 x 19l.)
	Dimensions W x D x H	-	21.5 x 60 x 85 cm
	Feet distance W x D	-	21.5 x 34 cm
	Weight	-	17 kg
	Watt	-	170 W
	Amp	-	1.2 A
	Electrical Consumption (At 25°C Room temperature)	-	Cooling: 170 W/h Maintenance: 80 W/h
	2 tanks	Capacity	15 l. (2 x 7,5 l.)
Dimensions W x D x H		21.5 x 60 x 72 cm	43 x 60 x 85 cm
Feet distance W x D		21.5 x 34 cm	43 x 34 cm
Weight		22 kg	26 kg
Watt		190 W	180 W
Amp		1.3 A	1 A
Electrical Consumption (At 25°C Room temperature)		Cooling: 190 W/h Maintenance: 115 W/h	Cooling: 180 W/h Maintenance: 100 W/h
3 tanks		Capacity	-
	Dimensions W x D x H	-	65 x 60 x 85 cm
	Feet distance W x D	-	65 x 34 cm
	Weight	-	32 kg
	Watt	-	220 W
	Amp	-	1.3 A
	Electrical Consumption (At 25°C Room temperature)	-	Cooling: 220 W/h Maintenance: 120 W/h



COOL XS

COOL

TANK & TAP & LID

Standard tap

Smart

Smart

Easy bayonet tap disassembly



Optional tap

Touchless

Touchless

Hinged lid



LIGHTING (Optional)

Light



RGB colour options



CUSTOMIZATION

Easy customization with stickers



Lid Flavour Tag (optional)



PERFORMANCE

Vertical Ventilation



Smart Cooling system



Direct expansion evaporator



Parts to clean per tank

6

5

CAPACITY

Type of consumption

LOW

HIGH

Single bowl version



Doble bowl version



Triple bowl version





COOL XS

COOL

up to **7,5 l.**
SMALL
Bowl capacity

up to **19 l.**
LARGE
Bowl capacity

30
250 ml
portions/bowl

76
250 ml
portions/bowl

Vertical Ventilation

Vertical Ventilation

Fast cooling technology

Fast cooling technology

BPA Free

BPA Free

Smart cooling system

Smart cooling system



www.v-air.es

an Ali Group Company



the spirit of excellence